

Serial No. 10/758,536  
 Docket No. YOR920030609US1  
 YOR.505

2

**AMENDMENTS TO THE CLAIMS:**

Please amend the claims as follows:

Claims 1-5. (Canceled).

Claim 6. (Previously Presented) A method of embedding an image into two images,

comprising:

performing a digital halftoning process on a Cartesian product of color spaces to embed the image into the two images,

wherein the digital halftoning process comprises an iterative isotropic halftoning process,

wherein the iterative isotropic halftoning process comprises:

for each iteration

for each i

for each j

for each output vector  $o = (o_1, o_2, o_3) \in P$

replace  $Outimage_k(i, j)$  with  $o_k$  for  $k = 1, 2, 3$ ,

set  $Error(o) = \sum_{k=1}^3 v_k \|L(Outimage_k - A_k)\|$

endfor

find output vector  $o_{min} = \arg \min_{o \in P} Error(o)$

Serial No. 10/758,536  
Docket No. YOR920030609US1  
YOR.505

3

set Outimage(i, j) =  $O_{min}$ .

endfor (j)

endfor (i)

wherein if Outimage has not changed between two iterations or maximum number of iterations reached, then exit the iterations loop,

where:

$A_1'$ ,  $A_2'$  and  $A_3'$  are input images;

P comprises a set of output vectors;

Output comprises  $A_1'$  and  $A_2'$  where  $(A_1, A_2, A_3) = \text{Outimage}$  which resembles  $(A_1', A_2',$

$A_3')$ ;

$v_i$  determines how strongly the error in each image is minimized; and

L comprises a linear space-invariant model of a human vision system.

Claim 7. (Original) The method of claim 6, wherein said Outimage is initialized using a random set of pixels.

Claim 8. (Original) The method of claim 6, wherein said Outimage is initialized using a uniform image of a single output vector.

Serial No. 10/758,536  
Docket No. YOR920030609US1  
YOR.505

4

Claim 9. (Original) The method of claim 6, wherein said Outimage is initialized by performing vector error diffusion.

Claim 10. (Original) The method of claim 6, wherein said Outimage is initialized by performing modified error diffusion.

Claim 11. (Currently Amended) The method of claim 6, wherein pixels of the input image is are within a convex hull of the output vectors.

Claim 12. (Original) The method of claim 6, further comprising gamut mapping the images.

Claim 13. (Currently Amended) The method of claim 12, wherein the gamut mapping comprises:

for  $p = (p_1, p_2, p_3) \in S$ ,

$M(p) = (s_1 p_1 + d_1, s_2 p_2 + d_2, s_3 p_3 + d_3)$

where:

$s_i$  comprise real numbers denoting scaling factors;

$p_i$  comprise pixels;

$S$  is a set of 3-tuples of pixels;

$M$  is a gamut mapping of a pixel  $P$ ; and

$d_i$  comprise offset vectors in the color space.

Serial No. 10/758,536  
 Docket No. YOR920030609US1  
 YOR.505

5

Claim 14. (Original) The method of claim 13, further comprising using the Qhull algorithm.

Claim 15. (Original) The method of claim 12, further comprising optimizing the gamut mapping.

Claim 16. (Currently Amended) The method of claim 15, wherein optimizing the gamut mapping comprises:

$$\max_{s_i, d_i} \min \left( \frac{s_1}{\alpha_1}, \frac{s_2}{\alpha_2}, \frac{s_3}{\alpha_3} \right) \text{ such that } M(S) \in H$$

wherein  $s_i$  comprise real numbers denoting scaling factors;

wherein  $\alpha_i$  is a "penalty" coefficient of scaling;

wherein  $M(S)$  is a mapping of set  $S$  of pixels; and

wherein  $H$  is the convex hull of the output vectors.

Claim 17. (Previously Presented) The method of claim 15, wherein the optimizing of the gamut mapping comprises:

$$\text{solving } \max_{s_i, d_i} s_1 s_2 s_3 \text{ such that } M(S) \in H,$$

wherein  $H$  comprises the convex hull of the output vectors.

Serial No. 10/758,536  
Docket No. YOR920030609US1  
YOR.505

6

Claims 18-32. (Canceled).